

EZ-TorQ II

Torque Analyzer

TORQUE ANALYZERS



KEY FEATURES

Accuracy $\pm 0.5\%$ of reading from 20% to 100%
Accuracy $\pm 1\%$ of reading from 10% to 20%

Recommended for hand screwdrivers, most wrenches and power tools (Not for use in testing Impact or Pulse type tools).

Selection of two operating modes: Track and Peak.

Seven units of torque measurements:
ozf.in, lbf.in, lbf.ft, cN.m, N.m, kgf.m, kgf.cm

Features built-in Quick Test operation.

Includes PC Windows based software program:
Mountz EZ-TorQ II Interface Program - to conduct Quick Tool Tests, Data Logging and Sensor Calibration.

"Flash" memory allows upgrades to be done by the user in the field & internet through the RS-232 port.

Easy to use Menu Structure.

Six-digit display.

Ability to download readings to PC via RS-232 or via USB.

Real time output via RS-232.

High Capacity Li-Ion Batteries for long life.

The unit will store a total of up to 150 data points.

Real time graph of torque vs. time using associated PC Windows software.

Features Go / No Go LEDs that illuminate when high or low tolerance setting is achieved or out of tolerance.

Two low-pass filter settings: 500 and 200 Hz.

Includes a Spring Run Down Adapter.

Includes a case, Universal Charger, 1/4 F/Hex Sq. Dr. Adapter, USB Adapter & RS232 Cable Adapter.

Dimensions: (L x W x H): 7 1/4" x 4 1/3" x 2"

NOTE!

Since a tester cannot always duplicate actual joint characteristics, the torque reading displayed on the EZ-TorQ may vary from the actual torque that a tool will apply to a joint. A run down adapter that simulates a variety of different joint characteristics is provided with the EZ-TorQ. When critical assemblies are involved, the torque output of the power tool being used should be verified on the actual assembly using a calibrated measuring torque tool.




CERTIFIED

Supplied with NIST-Traceable Certification of Calibration

RoHS CE

Model	Item #	Torque Ranges			Drive Size	Weight
		lbf.in	cN.m	kgf.cm		
EZ-TorQ II 10i	070800	1 - 10	11.3 - 113	1.2 - 11.5	17mm Female/Hex*	4.5 lbs.
EZ-TorQ II 50i	070801	5 - 50	56.5 - 565	5.8 - 57.6	17mm Female/Hex*	4.5 lbs.
EZ-TorQ II 100i	070802	10 - 100	113 - 1130	11.5 - 115	17mm Female/Hex*	4.5 lbs.
EZ-TorQ II 150i	070803	15 - 150	169.5 - 1695	17.3 - 173	17mm Female/Hex*	4.5 lbs.

* Each model includes a 1/4" Female/Hex Sq. Drive Adapter and a Spring Run Down Adapter for testing power tools.



ACCESSORIES

SCREW RUN DOWN ADAPTERS

Item #	Model	American	Metric	Quantity
600728-1*	RDA	2 - 56	M2x.4	5
600728-2*	RDA	4 - 40	M3x.5	5
600728-3*	RDA	6 - 32	M4x.7	5
600728-4*	RDA	8 - 32	M5x.8	5
600734-18*	RDA	5/16 - 18	-	5
600734-20*	RDA	1/4 - 20	-	5

* Hardware Kit # 1 for these RDA units (includes Washer and Screws), Item # 061237.

See EZ-TorQ manual for a list of items that are included in the Hardware Kit.



SPRING RUN DOWN ADAPTERS

Provides consistent and reliable torque readings for use with power driven torque control tools.

SEE PAGE 01.20



ACCESSORIES

Item #	Description
770300	Universal Charger*
600729	Case (Pictured Above)
603107	Battery Pack*
14-501830	Brush Cap
773064	RS-232 Cable
773069	Serial to USB Adapter
600727	1/4 F/Hex Sq. Dr Adapter (17mm F/Hex)
120143	Square Dr. Adapter (1/4 Sq. Dr x 1/4 Hex x 2" OAL)

* For EZ-TorQ II



CALIBRATION TEST EQUIPMENT

Calibrated Dead Weight and length are the official means by which Analyzers are traced to NIST, ISO etc.

SEE PAGE 01.18