



**Recommendations for Maintenance:**

Please, note it is important to make sure the tool has clean, dry and lubricated air at the recommended pressure supplied to it. (Please consult the service manual for further instructions)

The pulse tool requires preventive maintenance like oil changes and have the parts inspected periodically. It is recommended to make the first preventive maintenance at 250,000 pulses-seconds or 6 months, whichever one occurs first. The tool's performance should be evaluated. The oil needs to be changed. Inspect all the soft parts of the pulse unit (the soft parts are referenced as the "Repair Kit" - see parts list page 2). The Repair Kit includes all the necessary parts and it is recommended to be performed every six months (unless parts are in good condition). If the tool fails before the 250,000 pulses-seconds then the pulse unit needs to be rebuilt, with the "Repair Kit" and "Service Kit" (see parts list page 2).  
 Caution: prevailing torque, which makes that the tool start pulsing early, reduces the life of the Oil & O-rings of the pulse unit. A pulse-second is not every second the tool is running, only when it's "pulsing" and applying torque. On typical applications the tool should run down freely until fastener is snug and then the tool starts pulsing until it reaches the preset torque. When operating the tool on the fastener, start counting once the tool begins pulsing. You can use a watch with a second hand and time it until the tool shuts-off. Use the information to calculate how many pulse-seconds the tool performs per application each day. Then perform some basic math to calculate the tool's maintenance schedule. Use this formula.

$$\# \text{ Pulsing Seconds} \div \text{Total of Pulsing Time} = \text{No Cycles}$$

NOTE: Please include the rework, reverse, or retightening time is involve on the operation to calculate the accurate pulsing time. Here is an example:

Pulsing Time = 2 seconds  
 Pulses- seconds recommended = 250,000

$$250,000 \text{ pulses-sec} \div 2 \text{ sec} = 125,000 \text{ cycles}$$

Using the information above, you can estimate the maintenance period for the tool by using this formula:

No of Fasteners	Pulsing Time per Fastener	No of Parts Assembled per Day	Calculation	Maintenance Period
7	2 seconds	300	$125,000 / (300 \times 7) = 59$	59 days

Index No.	Part No.	Description	Qty	Index No.	Part No.	Description	Qty
1	63-757-026	Anvil Collar	1	42	63-00-41135	O-Ring	1
2	63-I40SD-419	Hold Spacer	1	43	63-I40-307	Rear Cover	1
3	63-I40SD-418	Spring	1	44	63-00-41144	O-Ring	2
4	63-I40SD-417	Quick change Hold	1	45	63-I60-101	Motor Housing	1
5	63-I100-410	Greasing Screw	1	46	63-I40S-108	Bushing	4
6	63-00-4153	O-Ring	1	47	63-I40S-102	Hanger	1
7	63-I60S-201	Pulse Unit Housing	1	48	63-00-41146	O-Ring	1
8	63-I40S-202	Bushing	1	49	63-I40-104	Nut	1
9	63-I40S-424	Washer	1	50	63-I40-504	Trigger	1
10	63-I60S-401	Pulse Cylinder Seat	1	51	63-00-3354	Spring Pin	1
11	63-00-41127	O-Ring	2	52	63-00-0505	Screw	2
12	63-I70-410	Greasing Screw	1	53	63-I100-503	Regulator Knob	1
13	63-00-41113	O-Ring	2	54	63-00-4101	O-Ring	1
14	63-00-3318	Spring Pin	2	55EA	63-IS40-505B	Valve Stem	1
15EA	63-I40S-403-B	Front Cover	1	56EA	63-I100-508B	Bushing	1
16	63-00-2602	X-Ring	1	57EA	63-00-41199	O-Ring	1
17	63-I40S-408	Front Plate	1	58EA	63-I40-507B	Spring	1
18	63-00-3813	Steel Ball	3	59	63-I100-506	Spring	1
19	63-I60SD-405	Anvil	1	60	63-I40-502	F/R Valve	1
20B	63-I60S-452	Roller	2	61	63-I40-501	Valve Sleeve	1
21B	63-I60S-406-B	Drive Blade	2	62	63-00-41111	O-Ring	2
22	63-I40S-407	Spring	2	63	63-I100-511	Pin	1
23	63-I40S-411	Valve Screw	1	64	63-00-41145	O-Ring	1
24C	63-IS60S-412-B	Valve	1	65	63-I40-601	Muffler	1
25	63-00-41130	O-Ring	1	66	63-I40-603	Exhaust Deflector	1
26	63-00-3435	Pin	2		63-I40-604A	Air Inlet 1/4"-19PF	
27C	63-I60S-404-B	Pulse Cylinder	1	67	63-I40-604B	Air Inlet 1/4"-19PT	1
28	63-00-3407	Pin	2		63-I40-604C	Air Inlet 1/4"-18NPT	
29	63-00-3436	Pin	1	68C	63-00-41173	O-Ring	1
30	63-I40S-415	Rear Plate	1	69C	63-IS40S-421	Pressure Valve	1
31	63-I40S-423	Washer	1	70C	63-I60S-453	Spring	1
32	63-I40S-402	Lock Nut	1	71C	63-I40S-454	Block Cap	1
33	63-I40S-306	Lock Nut	1	72EA	63-I40-409	Back-Up Ring	1
34	63-00-2348	Ball Bearing	1	※	63-I60DRK-E05A	Repair kit :Index No-	
35	63-I60-302	Cylinder	1			11(2); 13(2) ; 16; 22(2); 25	
36	63-00-3324	Spring Pin	1			68C;72EA	
37	63-00-3356	Spring Pin	1	※	63-I60DSK-E05A	Service kit :Index No-	
38	63-I60S-303	Rotor	1			17; 20B(2); 21B(2); 30;	
39	63-I60S-304	Rotor Blade	9			39(9); 56EA; 57EA; 58EA	
40	63-I40-305	Rear Plate	1	※	63-I60SD-400ASM	Pulse Unit	
41	63-00-2356	Ball Bearing	1		63-01-0505FL	Accessories Kits Included	
					63-Pulse Tool Fluid, 125ml	Pulse Tool Fluid, 125ml	