



Insulated

Torque Wrenches

KEY FEATURES

Designed and manufactured to meet or exceed the accuracy and repeatability requirements of ISO 6789:2003 ($\pm 4\%$ of setting).

May be used for torque on battery terminals.

Reduces possibility of shorting or shock.

PVC heat shrink insulation.

Non-conductive plastic grip handles.

For use on electrical systems up to 50 volts (SLO and MTBN models).

For use on electrical systems up to 1000 volts (TSN models).



ISO CERTIFIED COMPANY

Mountz is a ISO 9001 and ISO 17025 registered company dedicated to manufacturing and servicing high quality torque tools.

TSN - INTERNALLY PRESET

Model	Item #	Torque Ranges		Square Drive	Length		Weight	
		lbf.ft.	N.m		in.	mm	oz.	kg.
TSN25DI	020271	2 - 18	3 - 25	1/4"	8 7/8	226	15	0.42
TSN25AI	020272	2 - 18	3 - 25	3/8"	8 7/8	226	15	0.42
TSN55I	020273	10 - 40	15 - 55	3/8"	13	333	35	0.98
TSN125I	020274	30 - 90	40 - 125	1/2"	18 3/8	466	56	1.58

SLO - EXTERNALLY ADJUSTABLE

Model	Item #	Torque Ranges		Sq. Drive	Ratchet Dia.		Length		Weight	
		lbf.in	N.m		in.	mm	in.	mm	lbs.	kg.
SLO1/4I	060398	40 - 180	4 - 20	1/4"	1 1/2	38	8 5/8	220	1.3	0.6
SLO3/8I	060113	40 - 180	4 - 20	3/8"	1 1/2	38	8 5/8	220	1.3	0.6

MTBN - INTERNALLY PRESET

Model	Item #	Torque Ranges		Sq. Drive	Length		Weight	
		lbf.in	N.m		in.	mm	oz.	g.
MTBN2I	020592	1.8 - 18	0.2 - 2	1/4"	4 1/8	105	5.9	168
MTBN10I	020593	9 - 89	1 - 10	1/4"	4 1/8	105	5.9	168



NOTE!

Meets IEC900 Standards.

When ordering the TSN and MTBN models, the preset torque value must be provided.