



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2005

Mountz, Inc.

19051 Underwood Rd. Foley, AL 36535
 Anatoly Khesed Phone: 408 207 4339

CALIBRATION

Valid to: June 17, 2010

Certificate Number: AC-1333

I. Mechanical

PARAMETER/ EQUIPMENT	RANGE	BEST MEASUREMENT CAPABILITY [EXPRESSED AS UNCERTAINTY(+)]	REFERENCE STANDARD OR EQUIPMENT	METHOD(S)
Torque Transducer	(2 to 160) ozf·in (1 to 750) lbf·in (5 to 500) lbf·ft	0.086 ozf·in 0.44 lbf·in 0.86 lbf·ft	Lever Arms & Wheels, Dead Weights	3WI-7.6-003
Torque Transducer	(100 to 20 000) lbf·ft	14 lbf·ft	Reference Transducer, Digital Torque Tester, Reference Load Cells	3WI-7.6-004
Torque Hand Tools	(2 to 160) ozf·in (1 to 750) lbf·in (5 to 500) lbf·ft	0.086 ozf·in 0.44 lbf·in 0.86 lbf·ft	Reference Transducer, Digital Torque Tester	3WI-7.6-001
	(50 to 2 500) lbf·ft	2.7 lbf·ft		3WI-7.6-005
Torque Power Tools	(2 to 160) ozf·in (1 to 250) lbf·in (20 to 1 000) lbf·ft	0.086 ozf·in 0.44 lbf·in 0.86 lbf·ft	Reference Transducer, Digital Torque Tester.	3WI-7.6-002
	(75 to 7 500) lbf·ft	8.6 lbf·ft		3WI-7.6-006

Notes:

1. Best Measurement Uncertainties (Expanded Uncertainty) are based on approximately a 95% confidence interval, using a coverage of $k=2$
2. This scope is part of and must be included with the Certificate of Accreditation No.AC-xxxx

 Officer

