

RETW

Electronic Torque Wrench

KEY FEATURES

- Accuracy $\pm 2\%$ of reading ± 1 digit.
- Designed for daily screw tightening production environment.
- Program pre-set torque.
- Rotating head allows viewing of the display from any angle.
- Three units of torque measurement available: N.m, lbf.ft, lbf.in
- Selection of two operating modes: Track and Peak.
- Heavy duty ratchet head.
- Go/No Go LED's and a buzzer can be set for high or low torque limits.
- Four-digit display.
- Battery operation (Optional - Rechargeable Battery Adapter Kit).
- Optional RS-232 serial interface to download torque readings to a PC or printer in real-time.

Model	Item #	Torque Ranges		Length		Drive Type	Weight	
		American	S.I.	in.	mm		lbs.	kg.
RETW250i	290106	25 - 250 lbf.in	3 - 30 N.m	15	381	3/8" Sq Dr.	2.2	0.9
RETW100F	290107	10 - 100 lbf.ft	13.6 - 135.6 N.m	17	431	3/8" Sq Dr.	2.4	1.1
RETW150F	290108	15 - 150 lbf.ft	20.3 - 203.3 N.m	19	480	1/2" Sq Dr.	2.8	1.3
RETW250F	290109	25 - 250 lbf.ft	33.9 - 339 N.m	22	550	1/2" Sq Dr.	3	1.4



NOTE!

- Uses standard AA batteries (if not using Rechargeable Battery Adapter Kit accessory)
- Do not place alkaline batteries into Battery Charging Kit accessory. Only use rechargeable batteries with the kit.

RS-232 RECHARGEABLE BATTERY ADAPTER KIT

Item #290114

- RS-232 serial interface to download torque readings in real-time.
- Does not store any readings.
- Battery charger: ONLY use rechargeable batteries with the kit.



800.456.1828