



**Recommendations for Maintenance:**

Please, note it is important to make sure the tool has clean, dry and lubricated air at the recommended pressure supplied to it. (Please consult the service manual for further instructions)

The pulse tool requires preventive maintenance like oil changes and have the parts inspected periodically. It is recommended to make the first preventive maintenance at 250,000 pulses-seconds or 6 months, whichever one occurs first. The tool's performance should be evaluated. The oil needs to be changed. Inspect all the soft parts of the pulse unit (the soft parts are referenced as the "Repair Kit" - see parts list page 2). The Repair Kit includes all the necessary parts and it is recommended to be performed every six months (unless parts are in good condition). If the tool fails before the 250,000 pulses-seconds then the pulse unit needs to be rebuilt, with the "Repair Kit" and "Service Kit" (see parts list page 2).  
 Caution: prevailing torque, which makes that the tool start pulsing early, reduces the life of the Oil & O-rings of the pulse unit. A pulse-second is not every second the tool is running, only when it's "pulsing" and applying torque. On typical applications the tool should run down freely until fastener is snug and then the tool starts pulsing until it reaches the preset torque. When operating the tool on the fastener, start counting once the tool begins pulsing. You can use a watch with a second hand and time it until the tool shuts-off. Use the information to calculate how many pulse-seconds the tool performs per application each day. Then perform some basic math to calculate the tool's maintenance schedule. Use this formula.

**# Pulsing Seconds ÷ Total of Pulsing Time = No Cycles**

NOTE: Please include the rework, reverse, or retightening time involved on the operation to calculate the accurate pulsing time. Here is an example:

Pulsing Time = 2 seconds  
 Pulses- seconds recommended = 250,000

**250,000 pulses-sec ÷ 2 sec = 125,000 cycles**

Using the information above, you can estimate the maintenance period for the tool by using this formula:

No of Fasteners	Pulsing Time per Fastener	No of Parts Assembled per Day	Calculation	Maintenance Period
7	2 seconds	300	125,000 / (300*7) = 59	59 days

Index No.	Part No.	Description	Q'ty	Index No.	Part No.	Description	Q'ty
1	63-I90-410	Greasing Screw	1	39	63-00-3813	Steel Ball	1
2	63-00-4153	O-Ring	1	40	63-305F-034	Spring	1
3	63-I70S-201	Pulse Unit Housing	1	41	63-I40S-502	F/R Valve	1
4	63-I40S-202	Bushing	1	42	63-00-41146	O-Ring	1
5	63-I40S-424	Washer	1	43	63-00-41125	O-Ring	1
6	63-I70-401	Pulse Cylinder Seat	1	44	63-I40S-309	Seat	1
7	63-00-41160	O-Ring	2	45	63-00-0507	Screw	1
8	63-I70-410	Greasing Screw	1	46	63-I40S-503	Regulator Knob	1
9	63-00-41113	O-Ring	2	47	63-I70S-101	Motor Housing	1
10	63-00-3318	Spring Pin	2	48	63-I40S-509	Bushing	1
11	63-I70-403	Front Cover	1	49	63-I40S-510	Pin	1
12	63-I70-409	Back Up Ring	1	50	63-I40S-504	Trigger	1
13	63-00-2602	X-Ring	1	51	63-00-3306	Spring Pin	1
14EC	63-I80-411	Valve Screw	1	52	63-I40S-102	Hanger	1
15D	63-IS70-412-B	Valve	1	53	63-I40S-108	Bushing	2
16	63-00-41130	O-Ring	1	54	63-I40S-103	Housing Rubber	1
17	63-00-3435	Pin	2	55	63-00-41127	O-Ring	1
18	63-I70-408	Front Plate	1	56	63-I40S-508	Bushing	1
19EB	63-I70-405-B	Anvil	1	57	63-305C-021	Valve Stem	1
20B	63-I70-452	Roller	2	58	63-I40S-507	Spring	1
21B	63-I70-406-B	Drive Blade	2	59	63-I40S-601	Muffler	1
22	63-I70-407	Spring	2	60	63-I40S-603	Exhaust Deflector	1
23C	63-I70-404-B	Pulse Cylinder	1		63-I40S-604A	Air Inlet 1/4"PF	
24	63-00-3436	Pin	1	61	63-I40S-604B	Air Inlet 1/4"PT	1
25	63-00-3407	Pin	2		63-I40S-604C	Air Inlet 1/4"NPT	
26	63-I70-415	Rear Plate	1	62	63-00-3509	Snap Ring	1
27	63-I40S-423	Washer	1	63C	63-00-41173	O-Ring	1
28	63-I70-402	Lock Nut	1	64C	63-IS40S-421	Pressure Valve	1
29	63-I70S-306	Lock Nut	1	65C	63-I70S-453	Spring	1
30	63-00-2348	Ball Bearing	1	66C	63-I40S-454	Block Cap	1
31	63-00-3324	Spring Pin	1	67EC	63-I80-422	Back Up Ring	1
32	63-I70S-302	Cylinder	1	※	63-I70SSK-MZ	Service kit :Index No-	
33	63-I70S-303	Rotor	1			18; 20B(2); 21B(2); 26; 34(9);	
34	63-I70S-304	Rotor Blade	9			56; 57; 58	
35	63-00-3326	Spring Pin	1	※	63-I70SRK-MZ	Repair kit :Index No-	
36	63-I50S-305	Rear Plate	1			7(2); 9(2); 12; 13; 16; 22(2); 63C	
37	63-00-2356	Ball Bearing	1	※	# Pulse Tool Fluid, 125ml	Pulse Tool Fluid 125ml	
38	63-I40S-310	Air Inlet Plate	1		# Pulse Tool Fluid, 1000ml	Pulse Tool Fluid 1000ml	
※	<b>63-I70-400ASM</b>	Pulse unit : Index No- 6,7,8,9,10,11,12,13,14EC,15D,16,17,18,19EB,20B,21B,22,23C,24,25,26,28,63C,64C,65C,66C,67EC					