

Pistol Pulse Tools

Auto Shut-Off & Non Shut-Off

flexPower
by mountz



KEY FEATURES

- Various models that range from 4.4 - 332 lbf.ft
- Designed to enhance cycle time with high-speed rundown.
- Excellent power-to-weight ratio.
- Safe ergonomic selection - low noise decibels, minimal vibration & reaction free operation.
- Comfortable rubberized non-slip grips for easy handling and excellent thermal ergonomics.
- Specially designed pulse fluid extends life between oil changes - provides better stability. Double sealing increases performance - reduces maintenance.
- Shut-off and non shut-off models.
- Ergonomically safer than harmful hammering and vibration of impact wrenches.
- Pin Dentent included with square drive models.

AUTO SHUT-OFF		NON SHUT-OFF		Drive Type	Torque Ranges		Free Speed (RPM)	Weight		P/W Ratio Nm/ Kgs.	Length in.	Noise Level dBA	Average Air Consumption		Hose Size mm
Model	Item #	Model	Item #		lbf.ft	N.m		lbs.	Kgs.				m ³ /min. CMM	ft ³ /min. CFM	
FLEXS-30P	360168	FLEX-30P	360169	3/8" Sq Dr	4.4 - 9.2	6 - 12.5	4400	2.0	0.88	14.2	6.7	78.0	0.25	8.80	6.5
FLEXS-30PX	360100	FLEX-30PX	360111	1/4" F/Hex	4.4 - 9.2	6 - 12.5	4400	2.0	0.88	14.2	6.7	78.0	0.25	8.80	6.5
FLEXS-40PX	360101	FLEX-40PX	360112	1/4" F/Hex	7.4 - 13.2	10 - 18	4400	2.0	0.91	19.8	6.7	78.0	0.25	8.80	6.5
FLEXS-40P	360102	FLEX-40P	360113	3/8" Sq Dr	8.1 - 14	11 - 19	4400	2.0	0.91	20.9	6.6	78.0	0.25	8.80	6.5
FLEXS-50PX	360103	FLEX-50PX	360114	1/4" F/Hex	10.3 - 19.1	14 - 26	7200	2.0	0.91	28.6	6.7	80.0	0.35	12.30	6.5
FLEXS-50P	360104	FLEX-50P	360115	3/8" Sq Dr	11.1 - 19.9	15 - 27	7200	2.0	0.91	29.7	6.6	80.0	0.35	12.30	6.5
FLEXS-60PX	360105	FLEX-60PX	360116	1/4" F/Hex	14.8 - 22.1	20 - 30	6200	2.2	1.00	30.0	7.1	82.0	0.40	14.10	8
FLEXS-60P	360106	FLEX-60P	360117	3/8" Sq Dr	16.2 - 25.8	22 - 35	6200	2.2	0.91	38.5	7.0	82.0	0.40	14.10	8
FLEXS-65P	360154	FLEX-65P	360158	3/8" Sq Dr	21.4 - 32.2	29 - 45	4800	2.4	1.1	41.7	7.4	82.0	0.43	15.20	8
FLEXS-70PX	360166	FLEX-70PX	360167	1/4" F/Hex	22.8 - 34.6	31 - 47	7200	3	1.4	34.8	7.8	82.0	0.45	15.90	8
FLEXS-70P	360155	FLEX-70P	360159	3/8" Sq Dr	25.8 - 39.8	35 - 54	5400	2.4	1.1	50.0	7.4	82.0	0.45	15.90	8
FLEXS-80P	360156	FLEX-80P	360160	3/8" Sq Dr	35.4 - 50.1	48 - 68	5400	2.7	1.2	56.2	7.6	82.0	0.50	17.60	8
FLEXS-90P	360108	FLEX-90P	360119	1/2" Sq Dr	47.2 - 66.4	64 - 90	5400	3.4	1.55	58.1	7.9	83.0	0.53	18.70	8
FLEXS-100P	360109	FLEX-100P	360120	1/2" Sq Dr	62.7 - 88.5	85 - 120	5300	4.1	1.86	64.6	8.2	84.0	0.55	19.40	8
FLEXS-130P	360110	FLEX-130P	360121	1/2" Sq Dr	90.7 - 109.2	123 - 148	3600	5.0	2.25	65.8	8.5	86.0	0.73	25.60	11
FLEXS-150P	360152	FLEX-150P	360153	3/4" Sq Dr	121.7 - 154.9	165 - 210	3600	6.83	3.1	67.7	9.3	86.0	0.73	25.60	11
FLEXS-180P	360157	FLEX-180P	360161	3/4" Sq Dr	132.8 - 188	180 - 255	2700	8.4	3.8	67.1	10.4	86.0	0.73	25.60	11
FLEXS-200P	360171	FLEX-200P	360172	3/4" Sq Dr	177 - 332	240 - 450	3000	9.4	4.3	105.9	9.9	88.0	1.38	48.78	13

NOTE!

Recommended air pressure is 85 PSI. Use a high quality air filter regulator and lubricator to ensure stable air pressure for optimal performance and for removal of moisture and other potential debris that can reduce the longevity and performance of pneumatic tools.

All specified torque ranges were established statically on a Mountz (TorqueLab LTT Series) torque meter at a dynamic air pressure of 85 PSI (Pounds per Square Inch). The specified results should be used as guidance only in tool selection. In general, the torque range will be lower based on type of joint, air pressure, extension bars and/or extended sockets. A pulse tool is a discontinuous tool and added adapters or extensions create a dampening effect, thus lowering torque values. Tool selection as well as set up is recommended to be validated on the actual joint by use of a suitable calibrated torque wrench. We recommend a quality Mountz Digital torque wrench.