



Product Bulletin



Follow us on Twitter @mountztorque

PB # 0073 March 2016

www.mountztorque.com

PSE

Preset Torque Limiting Screwdrivers



Key Features

- Designed and manufactured to meet or exceed the accuracy and repeatability requirements of ISO 6789: 2003 (+/- 6% of setting).
- Various models that range from 5.7 ozf.in - 120 lbf.in
- Ergonomic rubber hand grip.
- Precision radial ball clutch "slips-free" when the preset torque is reached preventing over-torquing.
- Tamper-proof internal adjustment. No external adjustment scale - must be preset using a torque analyzer.
- Thrust bearings insure that the torque setting is independent of any end load applied by the operator.
- All models provide bi-directional operation and are calibrated in either the CW or CCW direction.
- ESD compliant.

Torque Ranges

Model	Item #	Torque Ranges			Drive	Color	Weight	
		American	S.I.	Metric			oz.	gm
PSE25	020186	5.7 - 35 ozf.in	4 - 25 cN.m	0.4 - 2.5 kgf.cm	1/4" F/Hex	Gold	3.2	91
PSE150	020173	1.8 - 13 lbf.in	20 - 150 cN.m	2.1 - 15.3 kgf.cm	1/4" F/Hex	Red	6.5	185
PSE450	020187	4.4 - 40 lbf.in	50 - 450 cN.m	5.1 - 45.8 kgf.cm	1/4" F/Hex	Green	7.1	202
PSE1350*	020188	22 - 120 lbf.in	2.5- 13.5 N.m	25.3 - 138 kgf.cm	1/4" F/Hex	Blue	8	229

Note! *PSE1350 is supplied with removable sliding T-bar

