



Product Bulletin



Follow us on Twitter @mountztorque

PB # 0065 June 2015

www.mountztorque.com

TLS Prime

Preset Torque Screwdriver

Key Features

- Accuracy +/- 10% of setting
- Two models that range from 1.8 - 40 lbf.in.
- Designed for low volume fastening applications. Limited to 2,000 life cycles.
- One-way clutch system is designed for the screwdriver to apply torque in one direction and lockup in the opposite direction for easy screw removal. Ideal for maintenance and refurbishing applications.
- Built with a cam-over design, the accurate torque screwdriver prevents a fastener or bolt from being under and over tightened.
- Ergonomic grip for the operator: lightweight and reduces operator fatigue.
- Simple torque adjustment design. No external adjustment scale - must be preset using a torque analyzer.
- Quick conversion from 1/4 F/Hex to 1/4 Sq Drive with accessory # 020175.



Torque Ranges

Model	Item #	Torque Ranges			Drive	Length		Weight	
		lbf.in	N.m	kgf.cm		in.	mm	oz.	gm.
TLS Prime 150	020700	1.8 - 13	0.2 - 1.5	2 - 15.3	1/4 F/Hex	5.4	138	7	198
TLS Prime 450	020701	4.5 - 40	0.5 - 4.5	5.1 - 45.9	1/4 F/Hex	5.4	138	7	198