

# FlexC

Cordless Torque Controlled Screwdrivers

**flexC Power**  
by mountz

POWER TOOLS

## KEY FEATURES

Various models that range from 8.8 - 265.5 lbf.in.

Built for torque control and durability, the cordless torque tools feature a high capacity lithium-ion battery.

Ideal for applications where air or electric power is not easily accessible.

Precision auto shut-off clutch for accurate repeatability.

Runs down about 1200-1400 fasteners (depending on joint and length of fastener) before recharge.

Audible and visual alarms alert operator for torque completion.

Low battery warning beep and auto tool shutdown when power diminishes.

Trigger repeat protection (0.7 seconds).

Easy torque adjustment on clutch (adjustment tool included).  
Protects from incidental or operator tampering of torque setting.

LED lamp illuminates work area.

Quick change battery.

## Right Angle Models

High performance brushless motor design that provides durability and reduces the standard maintenance costs for cordless screwdrivers.

Adjustable head positions.

Right Angle models (only) include three different colored rings, which allows color coding of specific torque values in production areas.



## NOTE!

Charger and battery are sold separately.

## ACCESSORIES

	Item #
FLEXC Li-ion Battery (10.8V 3.0Ah)	<b>360320</b>
FLEXC Li-ion Battery (14.4V 3.0Ah)	<b>360321</b>
Charger (100 - 240 VAC) for FLEXC Batteries (10.8V - 14.4V)	<b>360322</b>
Belt for FLEXC (Pistol Models)	<b>360325</b>

## PISTOL MODELS

Model	Item #	Torque Ranges		Length	Weight w/Battery
		lbf.in	N.m		
FLEXC-3PX	<b>360300</b>	8.8 - 30.9	1 - 3.5	7 7/8"	3.3 lbs.
FLEXC-8PX	<b>360301</b>	17.7 - 70.8	2 - 8	7 7/8"	3.3 lbs.
FLEXC-11PX	<b>360302</b>	26.5 - 97.3	3 - 11	7 7/8"	3.3 lbs.
FLEXC-12PX	<b>360303</b>	35.4 - 106.2	4 - 12	7 7/8"	3.3 lbs.

Model	Drive Size	RPM	Bolt Capacity	Li-ion Battery	Voltage
FLEXC-3PX	1/4" Female/Hex	1100	M3-M4	3.0 A.h.	10.8
FLEXC-8PX	1/4" Female/Hex	800	M4-M5	3.0 A.h.	10.8
FLEXC-11PX	1/4" Female/Hex	500	M4-M6	3.0 A.h.	10.8
FLEXC-12PX	1/4" Female/Hex	300	M4-M6	3.0 A.h.	10.8

## RIGHT ANGLE MODELS

Model	Item #	Torque Ranges		Length w/Battery	Weight w/Battery
		lbf.in	N.m		
FLEXC-8RX	<b>360304</b>	17.7 - 70.8	2 - 8	18"	4 lbs.
FLEXC-8R	<b>360305</b>	17.7 - 70.8	2 - 8	18"	4 lbs.
FLEXC-16RX	<b>360306</b>	44.3 - 141.6	5 - 16	18"	4 lbs.
FLEXC-16R	<b>360307</b>	44.3 - 141.6	5 - 16	18"	4 lbs.
FLEXC-30R	<b>360308</b>	70.8 - 265.5	8 - 30	18"	4.6 lbs.

Model	Drive Size	RPM	Bolt Capacity	Li-ion Battery	Voltage
FLEXC-8RX	1/4" Female/Hex	730	M4-M5	3.0 A.h.	10.8
FLEXC-8R	1/4" Square Drive	730	M4-M5	3.0 A.h.	10.8
FLEXC-16RX	1/4" Female/Hex	730	M5-M6	3.0 A.h.	10.8
FLEXC-16R	3/8" Square Drive	270	M5-M6	3.0 A.h.	10.8
FLEXC-30R	3/8" Square Drive	330	M6-M8	3.0 A.h.	14.4

FLEXC  
CORDLESS  
01.21



800.456.1828